

PTZ Mounts

Built-in SFP Install Base for PTZ Cameras



SBP-300HF

SBP-301HF

COMPATIBLE MODEL

Camera List	SNP-6320H/5430H	SNP-6321H/5321H
-------------	-----------------	-----------------

EXTERNAL CONNECTION

Alarm I/O	Input 4ea / Output 2ea
Remote Control Interface	RS-485/422
Audio	Input / Output, 3.5mm type
CVBS	BNC type, For installation
Power Line	24V AC, 2-wire

OPTICAL CHARACTERISTICS

Support SFP Voltage	3.3V typical
Support SFP Current	Max. 300mA
Support SFP Cage	Standard mini-SFP cage (For 6.5mm pitch SFP)
Support SFP Port Type	LC type
Required SFP Speed	1250Mbps (For 1000Mbps ethernet), 155Mbps (For 100Mbps ethernet)
Required SFP's BER (Bit Error Rate)	Max. 10^{-12}
Transmission Method (Optical)	Mode depends on SFP module
Optical Mode (Long / Short Wave)	Mode depends on SFP module
Cable Insertion Loss (dB)	Mode depends on SFP module

NETWORK CHARACTERISTICS

RJ-45 : Ethernet Speed	100Mbps
RJ-45 : Ethernet Physical Layer	100 Base-T
RJ-45 : Ethernet Standard	IEEE 802.3u support
Speed Transition (100 ↔ 1000Mbps)	External Dip switch
Fiber : Default Speed	1000Mbps
Fiber : Ethernet Speed	100Mbps, 1000Mbps
Fiber : Ethernet Physical Layer	100 Base-FX, 1000 Base-X
Fiber : Ethernet Standard	IEEE 802.3u, IEEE 802.3z support

NETWORK CHARACTERISTICS

Operating Temperature / Humidity	-50°C ~ +50°C (-58°F ~ 122°F) / Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10

ELECTRICAL

Power Consumption	Max. 65W, 3.1A (Heater on)
Input Voltage / Current	24V AC

MECHANICAL

Color / Material	Ivory / Aluminum
Dimension (WxH)	Ø163.9 x 157.9mm (Ø6.45" x 6.22"), Ø163.9 x 187.9mm (Ø6.45" x 6.7") (With NPT-Coupling)
Weight	1.1Kg (2.43 lb), 1.4Kg (3.09 lb) (With NPT-Coupling)

* The latest product information / specification can be found at www.samsungsecurity.com

Dimensions

Unit : mm (inch)

